
Data sheet



Resistor pack

DA314-4K7-2K2

Two resistors pre-wired, as below.



| Connections | |
|--|--|
| FL1 | Fly lead – 📕 green 100mm |
| FL2 | Fly lead – <mark>–</mark> yellow 100mm |
| FL3 | Fly lead – Field 100mm |
| R1 | 4Κ7Ω |
| R2 | 2Κ2Ω |
| Environmental | |
| Operating temperature | -10°C to +40°C |
| Storage temperature | -20°C to +50°C |
| Operating relative humidity | Maximum 95% non-condensing |
| Dimensions* | |
| Width | 10mm |
| Height | 18mm |
| Depth | 4mm |
| Weight | < 0.005Kg |
| Enclosure material | Polyolefil heat shrunk insulation |
| Finish | Black |
| Other | |
| Estimated mean time before failure (\ensuremath{MTBF}) | 50,000 hours |
| CE Approved | Yes |

*(+/- 2mm)

The enclosed information is believed to be correct. Information may change 'without notice' due to product improvement. Users should ensure that the product is suitable for their use. E&OE. Registered Proprietor: Benham (General Engineers) Ltd (No. 1181752) Registered at 3 Galliford Road Industrial Estate, Heybridge, Maldon, Essex CM9 4XD, UK. Directors: R.A.Scott, K.E.Horwood, T.J.Scott, N.J.Scott. VAT Reg. GB 28276273 Tel:+44(0)1621 856 850 Fax:+44(0)1621 856 162 sales@dantech.uk.com