

DA390

24V AC 4A Power supply
Within a mild steel enclosure

This multi-purpose metal cased power supply provides 8 x 24V AC 500mA via individually fused outputs.

Manufactured and tested in Britain, this range of power supplies has a five year warranty, allowing installers to fit and forget. It is ideal for where high reliability is required and where companies may have service or maintenance contracts for long periods of time.

Typical uses include powering CCTV cameras and camera housing heaters.

| Output | | |
|--|--|--------------------------|
| Voltage | 24V AC | |
| Current | 8 x 500mA | |
| Connection type | PCB terminal block (2.5mm²) | |
| Fused | 20 x 5mm 500mA quick blow glass fuse | |
| Input | | |
| Voltage | DA390-230V | DA390-110V |
| | 230V AC @ 50Hz (+/- 10%) | 110V AC @ 50Hz (+/- 10%) |
| Power consumption | < 125VA | |
| Connection type | 10mm² internal terminal block (3 x 1.5mm² or 2 x 2.5mm²) | |
| Fused | 3A Mains fuse (BS1362) | |
| Environmental | | |
| Operating temperature | -10°C to +40°C | |
| Storage temperature | -20°C to +50°C | |
| Operating relative humidity | Maximum 95% non-condensing | |
| Dimensions* | | |
| Width | 118mm | |
| Height | 275mm | |
| Depth | 70mm | |
| Weight | < 2.3Kg | |
| Enclosure material | Mild steel | |
| Finish | Powder coated RAL9016 (white) | |
| Other | | |
| Estimated operations before failure (MTBF) | 65,000 hours | |
| CE Approved | Yes | |

*(+/- 2mm)