

DA444

AC 16A power supply
Within a 19" 2U Rack-mount enclosure

A 19" rack mountable power supply with 24V AC 16A individually fused and indicated outputs. Typical uses include powering CCTV cameras, camera housing heaters.

Output			
	DA444- <i>x</i> -4	DA444- <i>x</i> -8	DA444- <i>x</i> -16
Voltage	24V AC	24V AC	24V AC
Current	4 x 4A	8 x 2A	16 x 1A
Connection type	PCB terminal block (2.5mm ²)		
Fused	20 x 5mm quick blow glass fuse rated to output current (e.g. DA444-8, 8 x 2A)		
Input			
	DA444- <i>x</i> -110V	DA444- <i>x</i> -110V	
Voltage	230V AC @ 50Hz (+/- 10%)	110V AC @ 50Hz (+/- 10%)	
Power consumption	< 500VA		
Connection type	C14 IEC connector (<i>Kettle lead</i>)		
Fused	6.3A Mains fuse (BS1362)		
Mains on indication	Neon lamp		
Environmental			
Operating temperature	-10°C to +40°C		
Storage temperature	-20°C to +50°C		
Operating relative humidity	Maximum 95% non-condensing		
Dimensions*			
Width	478mm (<i>19" Rack-mount</i>)		
Height	89mm (<i>2U Standard rack-mount</i>)		
Depth	248mm		
Weight	< 6.9Kg		
Enclosure material	Mild steel		
Finish	Powder coated black semi-gloss		
Other			
Estimated operations before failure (MTBF)	65,000 hours		
CE Approved	Yes		

*(+/- 2mm)